

IN THE CLAIMS

This listing of claims replaces all prior listings:


1. (Currently Amended) A display device ~~provided with~~comprising:
a plurality of light-emitting units stacked together between a cathode and an anode, each
of said light-emitting units including at least an organic light-emitting layer[[,]]; and ~~also with~~
a charge generation layer ~~held between each two adjacent ones of said~~ light-emitting
units,
wherein,
said charge generation layer is composed of a complex [[n]] oxide comprising at
least one [[of]] alkali metal ~~metals~~ and/or alkaline earth ~~metals~~ metal.
2. (Original) A display device according to claim 1, wherein said charge generation layer
is composed of Li_2SiO_3 .
3. (Original) A display device according to claim 1, wherein said charge generation layer
is formed of a mixed layer composed of Li_2SiO_3 and a charge transport material.
4. (Original) A display device according to claim 1, wherein said charge generation layer
has a stacked structure of a layer composed of Li_2SiO_3 and a mixed layer composed of Li_2SiO_3
and a charge transport material.
5. (Original) A display device according to claim 1, wherein said oxide in said charge
generation layer forms an interfacial layer on an anode side of said charge generation layer.

6. (Currently Amended) A display device according to claim 1, wherein said oxide comprising an alkali metal in said charge generation layer, ~~said oxide comprising said alkali metal~~, is at least one oxide selected from Li_2SiO_3 , Li_2CO_3 and Cs_2CO_3 .

7. (Currently Amended) A display device according to claim 1, ~~wherein further~~ comprising an interfacial layer on a cathode side of said charge generation layer that is composed of an organic material having ~~[[the]]~~ a phthalocyanine skeleton.

8. (Cancelled) ~~A display device according to claim 1, wherein said charge generation layer is insulative.~~

9. (Original) A display device according to claim 1, wherein said charge generation layer comprises an organic compound represented by the following formula (1):



..... Formula (1)

wherein R^1 to R^6 are each independently a substituent selected from a hydrogen atom, a halogen atom, a hydroxyl group, an amino group, an arylamino group, a substituted or unsubstituted carbonyl group having not more than 20 carbon atoms, a substituted or unsubstituted carbonyl ester group having not more than 20 carbon atoms, a substituted or unsubstituted alkyl group having not more than 20 carbon atoms, a substituted or unsubstituted

alkenyl group having not more than 20 carbon atoms, a substituted or unsubstituted alkoxy group having not more than 20 carbon atoms, a substituted or unsubstituted aryl group having not more than 30 carbon atoms, a substituted or unsubstituted heterocyclic group having not more than 30 carbon atoms, a nitrile group, a nitro group, a cyano group, or a silyl group; each two adjacent ones of R^m (m: 1 to 6) may be fused together via a cyclic structure associated therewith; and X^1 to X^6 are each independently a carbon or nitrogen atom.

10. (Original) A display device according to claim 9, wherein said metal oxide in said charge generation layer forms an interfacial layer on an anode side of said charge generation layer, and said organic compound forms an intrinsic charge generation layer arranged in contact with said interfacial layer.

11. (Currently Amended) A display device ~~provided with~~ comprising:

a plurality of light-emitting units stacked ~~together~~ between a cathode and an anode, each of said light-emitting units including at least an organic light-emitting layer[$[\cdot]$]; ~~and~~

~~also with~~ a charge generation layer ~~held~~ between each two adjacent ~~ones of~~ said light-emitting units[$[\cdot]$]; and

a first interfacial layer composed of a fluoride comprising at least one alkali metal or alkaline earth metal and located at an interface on an anode side of each charge generation layer.

~~wherein~~

~~at an interface on an anode side of each charge generation layer, an interfacial layer composed of a fluoride comprising at least one of alkali metals and alkaline earth metals is arranged.~~

12. (Currently Amended) A display device according to claim 11, wherein said interfacial layer ~~is formed of~~ comprises:

a conducting material layer; and


a layer arranged on an anode side of said conducting material layer and composed of a fluoride comprising at least one ~~[[of]]~~ alkali metals ~~and~~ or alkaline earth metal~~[[s]]~~.

13. (Currently Amended) A display device according to claim 12, wherein said conducting material layer comprises at least one of magnesium, silver ~~[[and]]~~ or aluminum.

14. (Currently Amended) A display device according to claim 11, ~~wherein~~ further comprising a second interfacial layer on a cathode side of said charge generation layer that is composed of an organic material having ~~[[the]]~~ a phthalocyanine skeleton.

15. (Cancelled)

16. (Original) A display device according to claim 11, wherein said charge generation layer comprises an organic compound represented by the following formula (1):



.... Formula (1)

wherein R^1 to R^6 are each independently a substituent selected from a hydrogen atom, a halogen atom, a hydroxyl group, an amino group, an arylamino group, a substituted or unsubstituted carbonyl group having not more than 20 carbon atoms, a substituted or unsubstituted carbonyl ester group having not more than 20 carbon atoms, a substituted or unsubstituted alkyl group having not more than 20 carbon atoms, a substituted or unsubstituted alkenyl group having not more than 20 carbon atoms, a substituted or unsubstituted alkoxy group having not more than 20 carbon atoms, a substituted or unsubstituted aryl group having not more than 30 carbon atoms, a substituted or unsubstituted heterocyclic group having not more than 30 carbon atoms, a nitrile group, a nitro group, a cyano group, or a silyl group; each two adjacent ones of R^m (m : 1 to 6) may be fused together via a cyclic structure associated therewith; and X^1 to X^6 are each independently a carbon or nitrogen atom.

17. (Currently Amended) A display device according to claim 16, wherein said interfacial layer is formed of a layer, ~~which is composed of~~ comprising:

a fluoride comprising at least one[[of]] alkali metals ~~and~~ or alkaline earth metal[[s,]]; and


a conducting material layer, arranged in this order from the side of said anode, ~~and~~

wherein,

said organic compound forms an intrinsic charge generation layer arranged in contact with said interfacial layer.

18. (Currently Amended) A display device ~~provided with~~comprising:
 a plurality of light-emitting units stacked together between a cathode and an anode, each of said light-emitting units including at least an organic light-emitting layer₁; and
~~also with~~ a charge generation layer held between each two adjacent ones ~~of said~~ light-emitting units,
 wherein,
 said charge generation layer is formed of:
 a mixed layer of at least one element of alkali metals ~~[[and]]~~or alkaline earth metals and an organic material₁ and
 an intrinsic charge generation layer₁
 stacked in contact with each other in this order from the side of said anode.

19. (Original) A display device according to claim 18, wherein said charge generation layer comprises an organic compound represented by the following formula (1):



.... Formula (1)

wherein R¹ to R⁶ are each independently a substituent selected from a hydrogen atom, a halogen atom, a hydroxyl group, an amino group, an arylamino group, a substituted or unsubstituted carbonyl group having not more than 20 carbon atoms, a substituted or unsubstituted carbonyl ester group having not more than 20 carbon atoms, a substituted or unsubstituted alkyl group having not more than 20 carbon atoms, a substituted or unsubstituted alkenyl group having not more than 20 carbon atoms, a substituted or unsubstituted alkoxy group having not more than 20 carbon atoms, a substituted or unsubstituted aryl group having not more than 30 carbon atoms, a substituted or unsubstituted heterocyclic group having not more than 30 carbon atoms, a nitrile group, a nitro group, a cyano group, or a silyl group; each two adjacent ones of R^m (m: 1 to 6) may be fused together via a cyclic structure associated therewith; and X¹ to X⁶ are each independently a carbon or nitrogen atom.

20. (Currently Amended) A display device according to claim 18, wherein ~~said at least one of~~ said alkali metals ~~[[and]]~~ or alkaline earth metals in said mixed layer amounts to not more than 50% in terms of relative film thickness percentage.

21. (Currently Amended) A display device according to claim 18, ~~wherein~~ further comprising at said interface on the anode side of said charge generation layer, an interfacial layer composed of a fluoride comprising at least one ~~[[of]]~~ alkali metals ~~and~~ or alkaline earth metals is arranged at said interface on an anode side of said charge generation layer.

22. (Currently Amended) A display device according to claim 18, ~~wherein~~ further comprising an interfacial layer on a cathode side of said charge generation layer is composed of an organic material having the phthalocyanine skeleton.